

Rack-mounted fans for 482.6 mm (19")




Accessories for climate control Page 454

Supply includes:

- Fully wired unit ready for connection
- Terminal strip and assembly parts

Approvals:

Available on the Internet



Air throughput, unimpeded air flow 320 – 480 m³/h

Model No.	Packs of	3340.230	3341.115	3341.230	3342.024	3342.230	3342.500	Page
With monitoring		-	-	-	-	-	■	
Rated operating voltage V, ~, Hz		230, 1~, 50/60	115, 1~, 50/60	230, 1~, 50/60	24 (DC)	230, 1~, 50/60	115 - 230, 1~, 50/60 24 (DC)	
Air throughput, unimpeded air flow m³/h		320	480	480	480	480	480	
No. of fans		2	3	3	3	3	3	
Distance between axes mm		85	85	85	105	105	105	
Rated current A		0.24 / 0.22	0.69 / 0.69	0.36 / 0.33	0.74	0.36 / 0.33	0.85	
Pre-fuse A		6	6	6	6	6	6	
Width mm		482.6	482.6	482.6	482.6	482.6	482.6	
Height mm		44	44	44	44	44	44	
Depth mm		200	200	200	200	200	200	
Operating temperature range		-10°C...+55°C	-10°C...+55°C	-10°C...+55°C	-10°C...+55°C	-10°C...+55°C	-10°C...+55°C	
Noise level dB(A)		51	52	51	51	51	51	
Weight kg		2.24	2.0	2.74	1.86	2.78	2.0	

Accessories

Digital enclosure internal temperature display and thermostat	1 pc(s).	3114.200	3114.200	3114.200	3114.200	3114.200	3114.200	466
Thermostat	1 pc(s).	3110.000	3110.000	3110.000	3110.000	3110.000	3110.000	467
Thermostat with strain relief	1 pc(s).	3110.100	3110.100	3110.100	3110.100	3110.100	3110.100	467
Speed control	1 pc(s).	3120.200	3120.200	3120.200	-	3120.200	-	470

Vario rack-mounted fans for 482.6 mm (19")




Accessories for climate control Page 454

Supply includes:

- Fully wired unit ready for connection
- Terminal strip and assembly parts

Approvals:

Available on the Internet



Air throughput, unimpeded air flow 320 – 480 m³/h

Model No.	Packs of	3350.230	3351.230	3352.230	3352.500	Page
With monitoring		-	-	-	■	
Rated operating voltage V, ~, Hz		230, 1~, 50/60	230, 1~, 50/60	230, 1~, 50/60	115 - 230, 1~, 50/60 24 (DC)	
Air throughput, unimpeded air flow m³/h		320	480	480	480	
No. of fans		2	3	3	3	
Distance between axes mm		85	85	105	105	
Rated current A		0.24 / 0.22	0.36 / 0.33	0.36 / 0.33	0.85 / 0.85	
Pre-fuse A		6	6	6	6	
Width mm		482.6	482.6	482.6	482.6	
Height mm		44	44	44	44	
Depth mm		200	200	200	200	
Operating temperature range		-10°C...+55°C	-10°C...+55°C	-10°C...+55°C	-10°C...+55°C	
Noise level dB(A)		51	51	51	51	
Weight kg		2.0	2.7	2.78	2.04	
Also required						
Guide frame	1 pc(s).	3355.100	3355.100	3355.100	3357.100	
Accessories						
Digital enclosure internal temperature display and thermostat	1 pc(s).	3114.200	3114.200	3114.200	3114.200	466
Thermostat	1 pc(s).	3110.000	3110.000	3110.000	3110.000	467
Thermostat with strain relief	1 pc(s).	3110.100	3110.100	3110.100	3110.100	467
Speed control	1 pc(s).	3120.200	3120.200	3120.200	-	470

Tangential fans for 482.6 mm (19")




Accessories for climate control Page 454

Supply includes:

- Fully wired unit ready for connection
- Filter mat

Approvals:

Available on the Internet



Air throughput, unimpeded air flow 320 m³/h

Model No.	Packs of	3144.000	Page
Rated operating voltage V, ~, Hz		230, 1~, 50/60	
Air throughput, unimpeded air flow m³/h		320	
Rated current A		0.16	
Power consumption W		37	
Width mm		482.6	
Height mm		88	
Depth mm		158	
Operating temperature range		-10°C...+55°C	
Noise level dB(A)		52	
Speed rpm		2245	
Maximum static pressure difference Pa		65 - 70	
Weight kg		2.02	
Accessories			
Digital enclosure internal temperature display and thermostat	1 pc(s).	3114.200	466
Thermostat	1 pc(s).	3110.000	467
Thermostat with strain relief	1 pc(s).	3110.100	467
Filter mats	5 pc(s).	3177.000	454
Front outlet grille 2 U	1 pc(s).	3176.000	459
Speed control	1 pc(s).	3120.200	470